


James Murray Supply  
P.O. Box 127  
Goodsoil, SK  
S0M 1A0

Ph: 306-238-2042  
Fx: 306-238-2043  
Cell: 306-238-7747  
jms-supply.com

**KOZ<sup>®</sup> PRODUCTS BV**

## SPECIFICATIONS KOZ CABLE MOUNTING CLAMPS TRI 3X 67-82 AND TRI 3X 82-98

- Application : suitable for fitting 3 single-conductor cables with high short-circuit load triangular arrays
- Range : for cables with nominal outer diameters of 67 to 98 mm
- Material : Polyamide, fiberglass-reinforced, black, resistance to UV rays, salt water, ozone, oils, fuels, alkalis and radioactive rays, halogen free, fully recyclable.
- Flame resistance : UL94 V-0 and classification following DIN 5510-2:2009 with flammability class S3, smoke SR2 and dripping ST-2.
- Standards : according to International Standard NEN-EN-IEC 61914:2009, Certificate of Conformity KOZ No 16881C by SGS.
- Flexure strength : 210 N/mm<sup>2</sup>
- Tensile strength : 120 N/mm<sup>2</sup>
- Thermal expansion : 0,01% per 10° C temperature increase.
- Temperature limits : Permanent application from -50° C to +120°. Brief heating up to 220°.
- Mechanical strength : tested at KEMA up to 42.000 N.
- Fitting : the central fastening hole in the bottom part of the KOZ TRI clamps means they can be fastened to e.g. masts and poles, as well as to concrete and fitting rails




Initial torque for fastening bolts, nuts, screws : 5 – 8 Nm  
(depends on cable manufacturer's prescription).

All tests have been done by KEMA Netherlands, SGS Belgium, Underwriters Laboratories Inc. and Schneider France.

All products listed in this catalogue are fully compliant manufactured with the EU Directive 2002/95/EG (RoHS) and Annex 2005/618/EG and 2005/717/EG. Meeting all legal obligations under REACH.

Dimensions in millimetres

Type	DØ	L	B	I	dØ	H	h	A	Weight/Gram
KOZ TRI 3x 67-82	67-82	252	100	202	16,5	140-175	70	26	1840
KOZ TRI 3x 82-98	82-98	284	100	234	16,5	168-205	78	26	2515



Fixing possibilities

No rights may be derived from the indicated sizes, as the products re subject to ongoing development. KOZ therefore reserves the right to implement these changes without notice. For the most up-to-date information, see our Internet site: [www.kozproducts.com](http://www.kozproducts.com)

